



1386-LGSMN

ISO Prox II Graphics Quality- standard card includes, 26 bit format, plain white glossy finish for direct card printing on front, with HID ISO Prox artwork with matte finish on back, printed



1386-LGSMN

ISO Prox II Graphics Quality- standard card includes, 26 bit format, plain white glossy finish for direct card printing on front, with HID ISO Prox artwork with matte finish on back, printed

Technical specifications

Technology

Credential type	Proximity
-----------------	-----------

Credential operating frequency	125 KHz
--------------------------------	---------

Support technology	125 HID Prox KHz
--------------------	------------------

System

Reading distance	more than 20 cm
------------------	-----------------

Card slot punch	No
-----------------	----

Printing

Direct surface printing	Yes
-------------------------	-----

Thermal transfer printing	Not recommended
---------------------------	-----------------

Ordering information

Minimum order quantity	100
------------------------	-----

Special card order form required	Yes
----------------------------------	-----

Physical

Surface cover	Glossy
---------------	--------

Material	PVC
----------	-----

Form factor	CR80 (Credit)
-------------	---------------

Physical dimensions	54 x 86 x 1 mm
---------------------	----------------

Net weight	5 g
------------	-----

Shipping weight	20 g
-----------------	------

Colour	White
--------	-------

Environmental

Operating temperature	-45 to 70°C
-----------------------	-------------

Storage temperature	-45 to 70°C
---------------------	-------------

Relative humidity	5 to 95% noncondensing
-------------------	------------------------

Standards & regulation

Compliance	RoHS
------------	------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 25 July 2019 - 13:20

