

5006PGGMN

Composite iCLASS SEOS Contactless Smart Card, 8 K Memory, Prog. With SIO, F-GLOSS, B-GLOSS, Sequential Matching Internal/External Card Numbering, No Slot Punch (Minimum



5006PGGMN

Composite iCLASS SEOS Contactless Smart Card, 8 K Memory, Prog. With SIO, F-GLOSS, B-GLOSS, Sequential Matching Internal/External Card Numbering, No Slot Punch (Minimum

Technical specifications

Technology

Credential type	Smart card
Credential operating frequency	13.56 MHz

System

Reading distance	1 to 5 cm
Custom data model	No
Memory size	8 kB
Card slot punch	Yes

Printing

Direct surface printing	Yes
Thermal transfer printing	Yes

Ordering information

Minimum order quantity	100
Cards/tags in package	1
Special card order form required	Yes

Physical

Surface cover	Glossy
Material	Composite
Form factor	CR80 (Credit)
Physical dimensions	54 x 86 x 1 mm
Net weight	5 g
Shipping weight	13 g
Colour	White

Environmental

Operating temperature	-40 to 70°C
Storage temperature	-40 to 70°C
Relative humidity	5 to 95% noncondensing

Standards & regulation

Compliance	RoHS
------------	------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 24 January 2019 - 18:48

