

TP-CP-KF-LG-25PK

(25 PACK) TRUPORTAL CREDENTIAL - SLENDER - TRUPORTAL LOGO- PROXIMITY (EM)

Product overview

These TruPortal keyfobs are to be used on T100A, T100B and any other UTC Fire & Security Transition reader supporting the CASI RUSCO Proximity protocol (CSN). The cards are unprogrammed and only the unique ID-number of the proximity chip, the so called Chip or Card Identification Number (CSN) is used by the readers.



Details

- Read only for CSN

TP-CP-KF-LG-25PK

(25 PACK) TRUPORTAL CREDENTIAL - SLENDER - TRUPORTAL LOGO- PROXIMITY (EM)

Technical specifications

Technology

Credential type	Proximity
Credential operating frequency	125 KHz
Support technology	125 GE ProxLite/CASI Prox KHz

System

Reading distance	5 to 10 cm
Custom data model	No
Card slot punch	No

Printing

Direct surface printing	No
Thermal transfer printing	No

Ordering information

Minimum order quantity	1
Cards/tags in package	25
Special card order form required	No

Physical

Surface cover	Glossy
Material	PVC
Form factor	KeyFob
Physical dimensions	105 x 115 x 32 mm
Net weight	270 g
Shipping weight	277 g
Colour	Orange

Environmental

Operating temperature	-10 to 45°C
Storage temperature	-10 to 45°C
Relative humidity	5 to 95% noncondensing

Standards & regulation

Compliance	RoHS
------------	------

Dimensions

	110 mm x 20 mm x 3 mm
--	-----------------------

Material

	PVC
--	-----

Frequency

	125 KHz
--	---------

Reading distance

	0-10 cm
--	---------

For use on

	T100A & T100B
--	---------------

Color

	Orange
--	--------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 11 February 2019 - 19:12

